

## Isolators

### MIS63-1 Series (With SIRIM Test Report)



2 Pole Isolator



3 Pole Isolator



3 Pole Isolator

Type	rating	cat. no.
2P	63A	MIS263N
<b>Width</b>		
2 module		
36mm		
<b>Packing size</b>		
box /carton		
6 / 60		

Type	rating	cat. no.
3P	63A	MIS363N
<b>Width</b>		
3 module		
54mm		
<b>Packing size</b>		
box /carton		
4 / 40		

Type	rating	cat. no.
3P	100A	MIS3100N
<b>Width</b>		
3 module		
54mm		
<b>Packing size</b>		
box /carton		
4 / 40		



Technical Data	
<b>Description</b>	
<ul style="list-style-type: none"> <li>Use as an isolating switch for an electrical circuit.</li> <li>Use in domestic, commercial and light industrial installations</li> </ul>	

<b>Electrical</b>	
Design according to	IEC 60947-3
Rated voltage	230/400V~, 240/415V~
Rated current	63, 100A
No. of poles	2, 3
Utilization category	AC22B
Conditional S.C.Current	6KA
Rated withstand current (Icw)	10In(Is)
Degree of protection	IP20
Electrical & mechanical	>4000 operating cycles

<b>Mechanical</b>	
Terminal capacity	1-25mm <sup>2</sup> (32 to 63A) 1-35mm <sup>2</sup> (100A)
Mounting installation	DIN rail EN 50022

<b>Dimension (mm)</b>	
3 Pole	54
2 Pole	36
32 - 63A	66.5
100A 3 Pole	66.5
100A 2 Pole	66.5
100A 1 Pole	66.5


## Colour Indicator Lights



Type	cat. no.
RYB	MIL
<b>Width</b>	
1 module	
18 mm	
<b>Dimensions</b>	
66.0	
1 Pole	
18	
84.0	

Technical Data	
<b>Electrical</b>	
Design according to	IEC 60947-5
Rated voltage	240V~
Frequency	50Hz
Degree of protection	IP20
<b>Mechanical</b>	
Terminal capacity	1-6 mm <sup>2</sup>
Mounting installation	DIN rail 50022

## Insulated Comb Bar



BUSBAR

Type	rating	cat. no.	no.pin
1p (with insulation)	60A	MB1PS - 60	56
2p (with insulation)	60A	MB2PS - 60	56
3p (with insulation)	60A	MB3PS - 60	54
4p (with insulation)	60A	MB4PS - 60	56
1p (with insulation)	100A	MB1PS - 100	56
3p (with insulation)	100A	MB3PS - 100	33